



SPECIFICATIONS

Capacity: 110,000 lbs. **Trailer Weight:** 20,225 lbs.

| | |
|---------------------|--|
| Deck Width | 8 ft. 6 in. Length: 25 ft. Height: 24 in. (Loaded) |
| Frame | Mainrails: Four fabricated 16" Deep cambered I-Beam, 80,000 P.S.I. steel, Boom Well |
| Crossmembers | 10" x 9 lbs. per ft. I-Beam, pierced through mainbeam (24" spacing Std.) |
| Gooseneck Length | Standard 102" (For special lengths contact sales) |
| Decking | 2" Nominal Apitong Decking with Expanded Metal Center |
| Wiring Harness | Sealed L.E.D. Lights & USA Star PLUS Sealed Modular Wiring Harness w/ 7-Way ATA Plug |
| Front Ramps | Front Flip w/ Grousers (Wood filled is available) |
| Hydraulics | Wetline hook-up for tractor PTO operation • REQUIREMENT: Low Flow/High Pressure System |
| Hydraulic Cylinders | Two Main 7.75", One 3" Locking, One 4" Gooseneck Support |
| Controls | Control Valve eye level |
| Lift Axle | Air Lift 3rd Axle |
| Tie Down | 7 per side - Patented "ROTO RINGS"® Swivel 360° |
| Outriggers | Cast Steel (Locks both in and out position) |
| Colors | Black, Yellow, Blue (standard) Imron Paint |

RUNNING GEAR

| | |
|---------------|--|
| Tires | Twelve 275/70R22.5 (H) Steel Belted Radial |
| Hubs/Wheels | Six Disc Type Hubs, Twelve 8.25 x 22.5 Disc Type Wheels, Stemco Oil Seals, Hub Piloted |
| Suspension | Air Ride (Combined Capacity 75,000 lbs.) Dump Valve, Air Lift 3rd Axle |
| Axles | Three 5" diameter 25,000 lbs. each, H.M. series bearings |
| Brakes | 16 1/2" x 7" Air, "S" Cam., Auto Slack Adjusters |
| ALL WHEEL ABS | Anti-lock brake system 4S3M, Sensors on (2) Axles, 3 modulator valves |
| Parking Brake | Spring Brakes on All Wheels |

OPTIONS

- Additional Deck Length: (26'-27'-28' Optional Lengths)
- Additional Deck Width: (108" w/ 102" axles or 108" axles) - (120" w/ 120" axles)
- Gooseneck Fenders
- Power Pack: 11hp, 12hp Kohler, 13hp Honda, or 16hp Kohler (Combination Power Pack/Wet Kit Available)
- Lockable Tool & Chain Storage: Forward center deck area (1 or 2 compartments)
- Additional "ROTO-RINGS"®
- Spare Tire & Disc Wheel 275/70R22.5 (H) Optional: Spare Tire Carrier
- Wheel Covers (Raised)
- Oak Decking in lieu of Apitong
- Paint (other than standard Black, Yellow, Blue) Price on Request

