

2018

HINO 268



TRUCKS

A Toyota Group Company

GVW: 25,950 LBS. BBC: 108"

ENGINE MODEL: HINO J08E-VB 260HP 660 LB- FT TORQUE (AVAILABLE)

KEY VOCATIONS: MOVING, PICK-UP AND DELIVERY, SANITATION

HINO INSIGHT CONNECTED VEHICLE



WWW.HINO.COM

YOUR VEHICLE IS CONNECTED, POWERON.

At Hino we're changing the way we support our vehicles and customers so that your business is first. From the moment you take delivery of your Hino Insight equipped connected vehicle, you're on the road to more uptime and lower operating costs. Combining Telematics, Remote Diagnostics and Case Management in one integrated platform, Hino Insight puts critical vehicle and driver management tools at your fingertips.

2018

HINO 268



ENGINE

	STD	OPT
Model	Hino J08E-WU	Hino J08E-VB (N/A with 152"WB)
Type	Diesel 4 cycle, 6-cylinder in-line water-cooled, dry cylinder liners	
Fuel System	Common rail, direct injection type (Denso)	
Max. output (SAE Gross)	230hp at 2,500 rpm	260hp at 2,500 rpm
Max. torque (SAE Gross)	520 lb.-ft. at 1,500 rpm	660 lb.-ft. at 1,500 rpm
Engine displacement: 8L		
Bore and stroke: 4.41 x 5.12 in.		

BRAKES

Service	Hydraulic system with disc brake for front and rear wheels
Exhaust	Electric-pneumatic with valve-in exhaust pipe
Parking	Lever control with cable, internal expanding drum type

FRAME

Ladder type	Straight C Channel	
Width	in.	34
Yield strength	PSI	80,000
Resisting bending moment in.-lbs. (one side, no reinforcement)	152"WB	All Others 1,280,000 1,031,900

WEIGHT CAPACITIES

Front axle	lbs.	10,000
Rear axle	lbs.	19,000
Front spring	lbs.	12,000
Rear Spring	lbs.	19,000

AXLE/SUSPENSION

Front axle	MFS-10 series reversed Elliot, "I" beam (oil lubricated)
Front spring	Taper-leaf spring, shock absorbers
Rear axle	RS19-145, full floating, single reduction, single-speed, hypoid gearing
Rear spring	Semi-elliptic main
Rear Air	OPT-Air ride suspension - Hendrickson OPT-Air ride suspension dump valve (electric), single & dual valve

ELECTRICAL EQUIPMENT

Batteries	STD- Two 12V parallel circuit, 1,300 CCA (650 X 2) (GR 31 type)
	OPT-Three parallel circuit, 1,950 CCA (650 x 3) (GR 31 type)
	OPT-Two parallel circuit 1,850 CCA (925 x 2) (AGM type)
Alternator	STD-12V, 130 A, Delco (brush type)
	OPT-12V, 135 A (brushless), 180 A (brush type), 200 A (brush type)
Starter	Denso-12V, 4.8 kW
Cab audio	Bluetooth AM/FM/CD Player/MP3

WHEELS/TIRES

6 Wheels	22.5 x 8.25 10-stud disc
6 tires	STD-11R22.5-14(G)
	OPT-255/70R22.5-16(H)
	OPT-295/75R22.5-14 (G)
Tire pattern	Fr- Rib, Rr - All Season

CHASSIS EQUIPMENT

Fuel tank	STD-50 gallon OPT-Dual 50 gal./Single 70 gal./Single 95 gal.
DEF tank	4.7 gallon

POPULAR OPTIONAL EQUIPMENT (partial list)

Allison Fuel Sense Plus / Max
Anti-siphon device insert in fuel tank
Back-up alarm
Cab paint, exterior - custom (factory)
Engine idle shutdown
Exhaust system - vertical stack type
Mirrors, fender mounted-chrome (both sides or passenger only)
Mirrors, outside rear view-chrome
Mirrors-power heated (available in chrome)
Power windows and door locks (available with keyless entry)
Programmable speed limit 65,70 mph
Rear helper spring-sub leaf type
Stabilizer bar, rear (leaf suspension only)
Wheels-polished aluminum or powder coated gray

SERVICES



ENGINE WARRANTY	STD - 5 years/250,000 miles	OPT - 7 years/150,000 miles
HINOCARE	OPT - Preventive Care	
HINOWATCH	24/7 Roadside Assistance	
HINO INSIGHT	Telematics by Telogis	STD 1 Year OPT 3 & 5 Yr
	Remote Diagnostics	STD 5 Years
	Case Management	STD 5 Years

DIMENSIONS/WEIGHTS

Wheelbase	in.	152/G	175/J	187/L	205/M	217/P	235/R	253/T	271/V
Cab to axle	in.	84.6	107.6	119.6	137.6	149.6	167.6	185.6	203.6
Frame height at front axle	in.	37.0	37.0	37.0	37.0	37.0	37.0	37.0	37.0
Frame height at rear axle - Air susp. / Leaf susp.	in.	39.0 / 39.8	39.0 / 39.8	39.0 / 39.8	39.0 / 39.8	39.0 / 39.8	39.0 / 39.8	39.0 / 39.8	39.0 / 39.8
Rear overhang	in.	50.0	63.0	75.0	75.0	97.0	97.0	97.0	79.0
Std. chassis weight - Leaf susp./230hp	lbs.	9,920	9,865	9,920	10,030	10,140	10,185	10,220	10,285
Std. chassis weight - Air susp./230hp	lbs.	9,890	9,810	9,865	9,975	10,085	10,130	10,165	10,230
Std. chassis weight - Leaf susp./260hp	lbs.	N/A	9,910	9,975	10,095	10,205	10,250	10,295	10,360
Std. chassis weight - Air susp./260hp	lbs.	N/A	9,855	9,920	10,040	10,150	10,195	10,240	10,315

POWERTRAIN AND PERFORMANCE

GVW		25,950 lbs.			
GCWR*		26,000 lbs.		33,000 lbs.***	
Powertrain	STD	OPT		OPT	
Gradeability (% of grade) 230hp/260hp	34.3 / 45.5	31.2 / 41.1	32.3 / 42.7	39.7 / 53.2	36 / 47.9
Rear axle gear ratios	5.57	5.13	5.29	5.57	5.13
Transmission	Model	Allison 2200 HS/RDS with Fuel Sense Basic		Allison 2500HS/2500RDS with Fuel Sense Basic	
	Type	Six speed automatic			
Ratios	1st.	3.102		3.512	
	2nd.	1.811		1.896	
	3rd.	1.406		1.439	
	4th.	1		1	
	5th.	0.712		0.737	
	6th.	0.61		0.64	
	Rev.	4.492		5.086	

All specifications of the products are with normal manufacturing allowances and tolerances. Hino Motors Sales, U.S.A., Inc. reserves the right to alter specifications at any time without previous notice.
 *Condition is city delivery and 8% max grades. ***24,200 lbs. when used in refuse application

HSS CON268 118

WWW.HINO.COM