



Aluminum Flatbed Trailers

American-Made Performance



The ultimate in performance, the Benson aluminum platform provides exceptional fuel economy, corrosion resistance and higher payload capacity. Known for its fleet-proven design, this trailer offers greater load and operating flexibility, lower maintenance and longer trailer life. After this trailer, you won't want to pull anything else.

Superior Main Beam. Lower Maintenance.

The two-piece, welded main beam design eliminates the need for mechanical fasteners by welding on the neutral axis of the main beam where bending stress is minimal. Unlike bolted designs, this main beam doesn't have fasteners, which eventually loosen, requiring additional maintenance over its lifetime.

Less Weight. More Freight.

Floor crossmembers weld to the main beam, side rail, and floor to form a super stiff structure, eliminating the need for knee braces for a lighter weight trailer and less maintenance.

Greater Flexibility. More Loaded Miles.

The Lock-Rite™ multi-position tie down system offers flexibility to either tie down narrow loads to the center of the trailer or to the outside siderails. This patent-pending design also allows the use of either straps or chain ties to secure loads. In addition, this flatbed comes standard with five additional crossmembers to support steel coil hauls. An optional full-length coil package is available.

Better Highway Visibility.

The enhanced visibility lighting system offers three stop/tail/turn lights and five dual-function side marker lights. The side marker lights also function as turn signals for improved motorist visibility. In addition, the one-piece, tubular bumper includes an extruded grip surface.





Aluminum Flatbed Trailers

American-Made Performance

General

- Length: 28' - 53'
- Width: 96" and 102"

Beam Rating(s)

- 524: 52,000 in 4' / 57,000 lb in 10' / 110,000 lb evenly distributed
- 724: 72,000 in 4' / 78,000 lb in 10' / 140,000 lb evenly distributed

Est. Base Weight(s)

- 524: 8,712 lb / 3,952 kg
- 724: 9,035 lb / 4,098 kg

Main Beam Design

- Welded, 2-piece, 6061 T6 extruded aluminum "T" cross sections
- Beams welded along neutral axis
- Floor sections welded to top flange of main beam
- Top tee extrusion with integral Lock-Rite™ groove
- Main beam camber cut in lower aluminum "T" section

Front End Design

- Bright finish, fabricated aluminum front crossmember
- Center mount glad hands and 7-way on removable access panel
- 5/16" steel coupler plate bolted to main beams and frame
- Heavy-duty cross and aft bracing

Rear End Design

- Closed section extruded rear light box
- Three rear stake pockets with extruded pocket protector
- Tubular bumper uprights with flanges for mounting accessories
- Extruded grip surface on top of bumper tube
- Rubber dock bumpers mounted vertically with three bolts
- Bumper assemblies are United States Department of Transportation (DOT) and Transport Canada compliant

Siderail Design

- Extruded box section side rail with integral Lock-Rite groove
- Radius edges to prevent strap damage
- "LL" sliding winch track roadside, bolt-on design
- Tumbled aluminum stake pockets on 24" centers

- Large diameter double pipe spools
- Extruded aluminum rub rail with recessed groove

Crossmember Design and Floor System

- 4-7/8" aluminum C-channel crossmembers on 16" centers
- 1-1/4" hollow core box design, extruded aluminum with four apitong nailers, two singles outside, a double in the center
- Crossmembers welded vertically to siderail and main beam; horizontally to floor
- Includes coil package with five additional aluminum crossmembers on 8" centers, optional full-length coil package is available

Undercarriage

- Lightweight, formed suspension crossmembers at suspension hangers and air springs
- Bolt-on, lower steel C-channel and strut bracing
- Air suspension with manufacturer's 5-year warranty, rated at 23,000 lb per axle
- 121" tandem widespread axle setting, large bearings, parallel "P" spindle wheel ends and axle alignment

Electrical Wiring / Lights

- Air and electrical accessible through removable front plate
- Below deck air and wire routing
- Enhanced visibility lighting system with recessed oval lights
- LED lights, five marker lights per side, flashing dual function side marker lights correspond with turn signals
- Anti-lock brake system (ABS)

Popular Options

- Additional air and electric configurations
- Additional aluminum components
- Specialized floor packages
- Alternate crossmember spacing
- Customized bumper filler plates
- Factory installed bulkheads
- Multiple accessories, freight securement and storage options
- Multiple axle configurations, sliding suspensions and lift axles

Base specifications are accurate at the time of publication, and are subject to change without notice. Custom options are available; please consult your Transcraft Corp. representative for additional information. ©2015 Transcraft Corporation, L.P. All rights reserved. Transcraft®, Benson® and Lock-Rite™ are marks owned by Wabash National, L.P.

CTP 0005 04.15

ORDERING INFORMATION

Call: 1-877-489-9020 ext. 1792
 Fax: 1-765-449-5320
 Email: sales@transcraft.com

Transcraft®



A Wabash National Company

Transcraft Corp.

489 International Drive
 Cadiz, KY 42211
 transcraft.com
 bensonflats.com